



## INFORMATIVE NOTE

Name: REFLEXX 46

Date: 05/03/2021 Rev: 015

### MANUFACTURER

REFLEXX SpA  
Via Passeri, 2 46019 VIADANA (MN)  
Tel.: + 39 0375 758891 Fax + 39 0375 464504 [info@reflexx.com](mailto:info@reflexx.com)  
[www.reflexx.com](http://www.reflexx.com)



### Imballo - Pack

100		10	
Taglia Size	Articolo Article	Taglia Size	Cartoni Cartons
R46 XS	REFLEXX 46 XS	XS	REFLEXX 46 XS
R46 S	REFLEXX 46 S	S	REFLEXX 46 S
R46 M	REFLEXX 46 M	M	REFLEXX 46 M
R46 L	REFLEXX 46 L	L	REFLEXX 46 L
R46 XL	REFLEXX 46 XL	XL	REFLEXX 46 XL

**DESCRIPTION:** ■ disposable examination glove powder free, not sterile ■ **Material:** natural latex ■ **Shape:** ambidextrous; five fingers, beaded cuff ■ **Colour:** white-amber ■ **Feature:** internally chlorinated; textured surface and textured finger ■ **Packing:** 100 pieces/box; 10 boxes/carton ■ **ISO 2859:** AQL 1.5 (Level G1) freedom from holes; AQL 2.5 (level G1) major defects; AQL 4 (level G1) minor defects

### CONFORMITY AND PERFORMANCES

#### Personal Protective Equipment cat III

0465 ANCI\_CIMAC, Via Aguzzafame, 60/b 27029 Vigevano (PV)  
Reg EU 2016/425 - EN ISO 374-1:2016 TYPE C - EN ISO 374-5:2016 - EN 374-2:2014 - EN 420:2003 + A1 2009

#### Medical Device

Reg EU 2017/745 - EN 455 1,2,3 & 4  
(CND T010201 NON SURGICAL LATEX GLOVES)  
- Complies with ASTM-F-1671 (viral penetration test) and ISO 10993-10 regulations (skin irritation and sensitization)



Reg CE 1935/2004 – Reg EU 10/2011 - DM 21/03/73. To such use carefully read the declaration of suitability for food contact (DICA).

DIMENSIONS		
Cod./Size	Length. min(mm)	Width. (±5 mm)
R46/ XS (6)	240	75
R46/ S (7)	240	85
R46/ M (8)	240	95
R46/ L (9)	240	106
R46/ XL (10)	240	116

Thickness mm	Palm (+/- 0.02)	0.10
--------------	-----------------	------

EN 455-2:2009/A1	Tensile strength	≥6 N
------------------	------------------	------

EN ISO 374-5:2016	Protection from microorganisms (bacteria and fungi)	pass
	Virus protection ISO 16604:2004	pass



EN ISO 374-1:2016				
Chemical compound:	COD	EN 16523-1:2015 TYPE C		EN 374-4:2013
		Performance level	Breakthrough time	% degradation
Sodium hydroxide 40%	K	3	>60'	5%

RISKS FROM WHICH THE DPI IS DESIGNED TO PROTECT:

COD	CAS:1310-73-2	Protection
K Sodium hydroxide 40%		Protection from use of inorganic bases

**RECOMENDATIONS OF USE** Multi-purpose glove to protect the hand and/or the handled product, can also be used for general uses ■ The glove is suitable for contact with pure chemical products for a period of less than the permeation time indicated in the chemical resistance table ■ Results obtained under laboratory conditions may not reflect actual working time **WARNINGS** Before using the product, try it in the real condition of use ■ The glove is a device subject to wear, so frequent replacement is recommended and in all cases where imperfections are observed ■ Wear gloves with dry, clean hands ■ The product contains natural latex which can cause allergic reactions of type I and IV hypersensitivity. In case of reaction, discontinue use and consult a doctor ■ The user must inform the manufacturer and the relative authority of any incidents occurring during the use of the protective equipment **STORAGE AND DISPOSAL** Store the gloves in their original packaging in a dry place. ■ Do not expose to direct sunlight and heat sources. ■ The expiry date is 3 years from the date of manufacture indicated on the sales package, and is valid for the product properly stored ■ Gloves must be disposed of according to local regulations ■ Declaration of Conformity on [www.reflexx.com](http://www.reflexx.com)

